



Installation Manual for Category 6E Shielded Tool-Less Keystone Jack HCS P/N J6E-00863 - Universal Wiring - FTP Cable



1 Remove 5 cm of the cable jacket.




2 Carefully remove the foil shield.
Make sure the drain wire remains intact.



3 Hold the wiring block with the colored side up and insert the pairs into place as shown below.




4 Insert the wires into the correct colored slots.



5 Cut the wires flush with a sharp tool.




6 Slide the wiring block into the the jack housing with the colored side down and push gently with your thumb. Note the guide and the IDC contacts.




7 Fold up the side caps.




8 Press the side caps firmly until they click and make sure both caps are securely closed.




9 Slide the metal shield over the jack. Note the correct orientation.



10 Wrap the drain-wire around the cable and close the metal shield.




11 Make sure the two grounding belts are inserted into the two slots.



12 Pull the grounding belts with a suitable pliers and fold them.



13 Wrap the ground wire and press tightly both grounding belts.



Note: Avoid damaging the cable when using the pliers and make sure the drain wire is in good contact with the keystone jack shield.



HES Cabling System



Installation Manual for Category 6E Shielded Tool-Less Keystone Jack HCS P/N J6E-00863 - Universal Wiring - S/STP Cable


1 Remove 5 cm of the cable jacket.




2 Fold back the braid shield.




3 Carefully remove all foil shields.




3 Hold the wiring block with the colored side up and insert the pairs into place as shown below.




4 Insert the wires into the correct colored slots.





5 Cut the wires flush with a sharp tool.




6 Slide the wiring block into the the jack housing with the colored side down and push gently with your thumb. Note the guide and the IDC contacts.




7 Fold up the side caps.




8 Press the side caps firmly until they click and make sure both caps are securely closed.



9 Slide the metal shield over the jack. Note the correct orientation.




10 Close the metal shield.




11 Make sure the two grounding belts are inserted into the two slots.



12 Pull the grounding belts with a suitable pliers and fold them.



13 Wrap the shield and press tightly both grounding belts.



Note: Avoid damaging the cable when using the pliers and make sure the braid shield is in good contact with the keystone jack shield.