

## 600x800 Free Standing Cabinets



### Description

HCS DataLine series includes a wide range of high quality racks, cabinets and enclosures, specially designed for structured premise cabling in local area networks (LANs), including distribution and equipment, cross connect cabinets and racks, splice boxes, climate control and many more components for both copper and fiber optic cabling systems.

HCS DataLine 10 600x800 Free Standing Cabinets are suitable for both office environments & equipment rooms, having an attractive design combined with a long-lasting, solid & stable construction, guaranteed by the HCS DataLine Logo & Trademark.

### Applications

The special design of HCS DataLine 10 Free Standing Cabinets allows the use of a large variety and types of accessories, including 19" panels, hubs and active equipment, fixed and/or sliding shelves, fan units, power strips, pulleys, grounding and potential equalization bus bars, lighting units, stacking kits, floor fixing kits, cable management panels, and many other 19" devices and accessories.

### Qualifications and Approvals

HCS DataLine 10 Free Standing Cabinets are supported by HCS DoubleSafe™ QA Program and they comply to the following standards:

General	Steel Sheets	Powder Coating	Mechanical	Assembly	IT equipment safety	Fan Unit & Power Strips
<ul style="list-style-type: none"> <li>▣ TS EN 60297-3-100/101/102</li> <li>▣ DIN 41494</li> <li>▣ TS EN 60529-1</li> <li>▣ IP20 (Optional IP 42)</li> </ul>	<ul style="list-style-type: none"> <li>▣ DIN EN 10130-91</li> <li>▣ DIN EN 10327</li> <li>▣ EREĞLİ 6112</li> </ul>	<ul style="list-style-type: none"> <li>▣ DIN 67530</li> <li>▣ ASTM D 2796</li> <li>▣ ASTM D 3451</li> </ul>	<ul style="list-style-type: none"> <li>▣ TS EN 61587-1</li> </ul>	<ul style="list-style-type: none"> <li>▣ TS EN 60917-2-1/-2</li> </ul>	<ul style="list-style-type: none"> <li>▣ TS EN 60950-1</li> <li>▣ IEC 60364-7-707</li> </ul>	<ul style="list-style-type: none"> <li>▣ TS EN 60439-1</li> <li>▣ TS EN 62208</li> </ul>

## 600x800 Free Standing Cabinets

**Benefits & Features**

- ❑ Solid and stable construction- providing support for large loads.
- ❑ Aesthetic & attractive design - for use in open office environments.
- ❑ Flat packed design option- providing minimal storage space and saving transportation costs.
- ❑ Large cable spaces - enabling easy and comfortable installation of many cables.
- ❑ Sophisticated cable channeling - enabling concealed cords routing.
- ❑ Clear u-marking inside the cabinets - enabling easy & simple profile installation planning.
- ❑ Removable side panels via handles - enabling fast & easy cabinet stacking.
- ❑ Removable side, front and rear doors- allows using cabinet as a relay rack.
- ❑ Adjustable profile positioning inside the cabinets - enabling efficient installation of different size devices.
- ❑ Vented top cover- allows passive ventilation.
- ❑ Stackable construction - allows to proper installation many cabinets side to side.
- ❑ PVC stoppers - avoid metal surface noise while side panels are mounted.


## 600x800 Free Standing Cabinets



### General Properties

Material of Construction	Sheet & Galvanized steel. 1.0/1.2/1.5/2.0 mm thickness.
Paint and Color	Special steel finish with electrostatic powder coat, RAL 9005 black. Other colors available upon request.
Front Door	Smoked, secured and tempered glass within metal frame, one part, 4 mm. thick, reinforced with metal frame. Opening left & right. 180 degree opening (135 degree when used in row). Interchangeable door hinges.
Side Panels	Removable with handles & lockable with slim latch.
Rear Door	Solid metal, Removable and key lockable, 1 part. 65x300 mm cable entry with cover (brush mountable instead of cover). 180 degree opening (135 degree when used in row). Interchangeable door hinges.
Top Chasis	Monoblock, welded, CDx form construction. Fan tray mountable. Vented from sides for ventilation. 300x65 mm space for cable entry from top (brush mountable).
Top Cover	Monoblock, welded, CD form construction. 20mm spacing above the cabinet top for ventilation. 300x65 mm cable entry with cover (brush mountable instead of cover). Fixing possibility to ceiling (with fixing accessory).
Bottom Chasis	Monoblock, welded, CDx form construction. Fixing points either fixing to floor or raised floor. 300x300 mm adjustable space for cable entry from bottom, brush mounted.
19" profiles	Adjustable, 4 units (2 front, 2 rear). U-marked.
Vertical Cable Organizer	Mountable rear & side vertically (optional).
Front Door Lock	High quality, single point cylindrical locking mechanism with handle.
Levelling fit & Pulleys	Available (optional).
Loading Capacity	1000 kg max. (42U, TS EN 61587-1).

## 600x800 Free Standing Cabinets



### Ordering Information

HCS P/N	Description	Internal Height mm	Dimensions			Net Weight Kg	Notes
			Width mm	Depth mm	Height mm		
C10-02668	26U 19" Free Standing Cabinet	1169	600	800	1317	67,5	
C10-03268	32U 19" Free Standing Cabinet	1436	600	800	1584	78,0	
C10-03668	36U 19" Free Standing Cabinet	1613	600	800	1761	84,5	
C10-03968	39U 19" Free Standing Cabinet	1747	600	800	1895	88,0	
C10-04268	42U 19" Free Standing Cabinet	1880	600	800	2028	92,5	
C10-04468	44U 19" Free Standing Cabinet	1969	600	800	2117	96,0	
C10-04768	47U 19" Free Standing Cabinet	2102	600	800	2250	101,0	