

600x450 Wall Mount Cabinets



Description

HCS DataLine series includes a wide range of high quality racks, cabinets and enclosures, specially designed for structured premise cabling in local area networks (LANs), including distribution and equipment, cross connect cabinets and racks, splice boxes, climate control and many more components for both copper and fiber optic cabling systems.

HCS DataLine 20 600x450 Wall Mount Cabinets are suitable mainly for office environments & equipment rooms, having an attractive design combined with a long-lasting, solid & stable construction, guaranteed by the HCS DataLine Logo & Trademark.

Applications

The special design of HCS DataLine 20 Wall Mount Cabinets allows the use of a large variety and types of accessories, including 19" panels, hubs and active equipment, fixed and/or sliding shelves, fan units, power strips, pulleys, grounding and potential equalization bus bars, lighting units, stacking kits, floor fixing kits, cable management panels, and many other 19" devices and accessories.

Qualifications and Approvals

HCS DataLine Wall Mount Cabinets are supported by HCS DoubleSafe™ QA Program and they comply to the following standards:

General	Steel Sheets	Powder Coating	Mechanical	Assembly	IT equipment safety	Fan Unit & Power Strips
<ul style="list-style-type: none"> ▣ TS EN 60297-3-100/101/102 ▣ DIN 41494 ▣ TS EN 60529-1 ▣ IP20 (Optional IP 42) 	<ul style="list-style-type: none"> ▣ DIN EN 10130-91 ▣ DIN EN 10327 ▣ EREĞLİ 6112 	<ul style="list-style-type: none"> ▣ DIN 67530 ▣ ASTM D 2796 ▣ ASTM D 3451 	<ul style="list-style-type: none"> ▣ TS EN 61587-1 	<ul style="list-style-type: none"> ▣ TS EN 60917-2-1/-2 	<ul style="list-style-type: none"> ▣ TS EN 60950-1 ▣ IEC 60364-7-707 	<ul style="list-style-type: none"> ▣ TS EN 60439-1 ▣ TS EN 62208

600x450 Wall Mount Cabinets

**Benefits & Features**

- ❑ Solid and stable construction- providing support for large loads.
- ❑ Aesthetic & attractive design - for use in open office environments.
- ❑ Flat packed design option- providing minimal storage space and saving transportation costs.
- ❑ Large cable spaces - enabling easy and comfortable installation of many cables.
- ❑ Sophisticated cable channeling - enabling concealed cords routing.
- ❑ Clear u-marking inside the cabinets - enabling easy & simple profile installation planning.
- ❑ Removable side, front and rear doors - allows using cabinet as a relay rack.
- ❑ Adjustable profile positioning inside the cabinets - enabling efficient installation of different size devices.
- ❑ Vented top cover- allows passive ventilation.
- ❑ PVC stoppers - avoid metal surface noise while side panels are mounted.
- ❑ Pulleys and levelling fit mountable - enabling installation as free-standing cabinets.


600x450 Wall Mount Cabinets



General Properties

Material of Construction	Sheet & Galvanized steel. 1.0/1.2/1.5/2.0 mm thickness.
Paint and Color	Special steel finish with electrostatic powder coat, RAL 7035 grey. Other colors available upon request.
Front Door	Smoked, secured and tempered glass, 4 mm. thick, reinforced with metal frame. Interchangable (Left&right). 180 degree opening for single use, 135 degree opening in row.
Side Panels	Removable, complete metal. Single point cylindrical locking mechanism.
Rear Panel	Removable, complete metal. Mounting plate supported with welding. 65x150 mm cable entry hole (plate or brush mountable).
Top Chasis	Monoblock, welded, CDx form construction. Fan tray mountable. Sides vented for passive ventilation. 65x150 mm adjustable cable entry hole.
Bottom Chasis	Monoblock, welded, CDx form construction. 65x150 mm adjustable cable entry hole (brush mountable).
19" profiles	Adjustable, 2 units in the front. U-marked.
Vertical Cable Organizer	None.
Front Door Lock	High quality, single point cylindrical locking mechanism.
Levelling fit & Pulleys	Optional.
Loading Capacity	100 kg max. (12U, TS EN 61587-1)

600x450 Wall Mount Cabinets



Ordering Information

HCS P/N	Description	Internal Height mm	Dimensions			Net Weight Kg	Notes
			Width mm	Depth mm	Height mm		
C20-00764	7U 19" Wall Mount Cabinet	357	600	450	415	17,0	
C20-00964	9U 19" Wall Mount Cabinet	446	600	450	502	19,0	
C20-01264	12U 19" Wall Mount Cabinet	579	600	450	637	22,0	
C20-01564	15U 19" Wall Mount Cabinet	712	600	450	770	25,5	
C20-01864	18U 19" Wall Mount Cabinet	846	600	450	903	28,5	