



Description

HCS DataLight series includes a complete line of fiberoptic cables for high transmission rates including voice, data and video. All HCS DataLight cables are produced and rigorously tested to conform to most international standards. HCS DataLight Breakout cable (BRK) series consists of 2-36 minicables, cabled and jacketed with LSOH compounds. HCS DataLight cables fully conform to and provide a substantial margin above all relevant TIA and IEC standards. Optional fibers available: Multimode 50/125 microns (OM2, OM3, OM4 & OM5), 62.5/125 microns and Singlemode fibers.

Applications

HCS DataLight cables can be used for various application including the following:

- ☑ General purpose all-dielectric indoor LAN cable
- ☑ In-building backbone, riser or horizontal cabling
- ☑ Short distance distribution and direct termination
- ☑ Office wiring

HCS DataLight cables support all presently available LAN applications, including the IEEE802.3z protocols for Gigabit Ethernet, 1000BASE-SX (Short wavelength Gigabit Ethernet) 1000BASE-LX (Long wavelength Gigabit Ethernet) & IEEE 802.3ae 10GBASE-SR/SW 10GBASE-LX4 (10 Gigabit Ethernet).

Qualifications and Approvals

HCS DataLight Cables are tested and verified for full compliance with the following standards:

- ☑ ANSI/TIA-568.3-E
- ☑ ISO/IEC 11801
- ☑ CENELEC EN50173
- ☑ TIA-455
- ☑ IEC 60332-1
- ☑ IEC 60754
- ☑ IEC 60793
- ☑ IEC 60794

Benefits & Features

- ➔ Exceptional material properties and cable design - Providing a unique Century™ Lifetime Warranty.
- ➔ Tight 900 microns buffered fibers - Providing easy, fast and trouble-free termination and use of field-installable connectors.
- ➔ All-dielectric construction - Providing perfect EMC (Electro Magnetic Compatibility) and total noise immunity.
- ➔ Crisp and clear color coding - Providing positive fiber identification and ease of termination.
- ➔ Descending sequential meter mark - Providing easy stock and left-over handling.
- ➔ Smooth, limp and flexible jacket - Providing easy and comfortable cable handling.
- ➔ Batch number printed every meter - Providing fast retrieval of test results from data-base.
- ➔ A comprehensive product range - Providing all state-of-the-art cable constructions.
- ➔ Unique DoubleSafe™ Quality Assurance Program - Providing lowest rejection rate available.

OPTIONAL CONSTRUCTIONS

HCS DataLight Breakout Cables contain up to 36 color-coded minicables, each minicable consists of one optical fiber with a 0.9 mm tight or semi-tight buffer, reinforced by aramid and E-glass strength yarns and protected with a flame-retardant PVC or LSOH Jacket.

The minicables are cabled together (with fillers in case of need) around a dielectric central strength member (except when noted otherwise), wrapped with a plastic binder and overall covered with a flame-retardant PVC or LSOH Jacket.

Basic Fiber	As selected from the FIBER OPTIONS Section
Buffer Type	Tight or Semi-tight
Buffer Material	LSOH Halogen free or flame retardant PVC compound
Buffer OD	900 microns nom
Strength Elements	Served aramid and E-glass yarns
Individual Jacket Material	LSOH Halogen free flame retardant compound
Number of Minicables	2-36
Color Code	HCS Color Table No. 3 up to 12 minicables. (Larger fiber count: Numbered minicables)
Outer Jacket	LSOH Halogen free flame retardant compound
Standard Outer Jacket Color	Light Gray RAL 7035. Other colors available upon request
Standard Surface Marking	Includes HCS P/N, Cable Description, Meter Mark and Batch Number

*Detailed cable description is available in the relevant technical specification.

ORDERING INFORMATION

HCS P/N	Description	Buffer	OD mm ±10%	Weight kg/km ±10%
RFO-00203-DR0-Fx	2 Fibers LSOH gray	Tight	6.4	39
RFO-00403-DR0-Fx	4 Fibers LSOH gray	Tight	7.2	53
RFO-00407-DR0-Fx	4 Fibers LSOH gray	Tight	8.0	67
RFO-00603-DR0-Fx	6 Fibers LSOH gray	Tight	8.0	68
RFO-00803-DR0-Fx	8 Fibers LSOH gray	Tight	9.7	93
RFO-01203-DR0-Fx	12 Fibers LSOH gray	Tight	12.9	162
RFO-02403-DR0-Fx	24 Fibers LSOH gray	Tight	15.5	225
RFO-03603-DR0-Fx	36 Fibers LSOH gray	Tight	17.6	310

Notes:

1. Detailed P/N breakdown is provided [HERE](#).
2. "FO" in the P/N is replaced by the fiber designation selected from the **FIBER OPTIONS** Table.
3. The default packaging is 2000m reels. Other packaging options to be discussed with HCS Customer Service.
4. The default jacket color of HCS standard cables is Light Gray RAL 7035. Other colors available.
5. CPR options available upon request, to be discussed with HCS Customer Service.
6. "x" shall be replaced by a letter (A to Z) in the cable part number indicated in the detailed technical specification.