

TRANSMISSION PROPERTIES AND ELECTRICAL SPECIFICATIONS

FREQ.	Insertion Loss			NEXT			PS NEXT			EL FEXT			PS EL FEXT			RL			TCL	EL TCL
MHz	dB/100m			dB			dB			dB/100m			dB/100m			dB			dB	dB
	Max	Nom	std	Min	Nom	std	Min	Nom	std	Min	Nom	std	Min	Nom	std	Min	Nom	Std	Min	Min
1.00	2.0	1.65	2.0	77.3	84.3	74.3	75.3	82.3	72.3	70.8	80	67.8	68.8	77	64.8	20.0	25	20.0	40	35
10.00	5.9	5.6	6.0	61.3	69.3	59.3	60.3	67.3	57.3	50.8	65	47.8	48.8	62	44.8	26.0	30	25.0	40	15
25.00	9.4	9.0	9.5	56.3	63.3	53.3	54.3	61.3	51.3	42.8	57	39.8	40.8	54	36.8	25.3	30	24.3	36	7.0
31.25	10.6	10.2	10.7	54.9	61.9	51.9	52.9	59.9	49.9	40.9	53	37.9	38.9	50	34.9	24.6	28	23.6	35.1	5.5
62.50	15.2	14.9	15.4	50.4	57.4	47.4	48.4	55.4	45.4	34.9	45	31.9	32.9	43	28.9	22.5	27	21.5	32	NS
100.00	19.6	19.2	19.8	47.3	54.3	44.3	45.3	52.3	42.3	30.8	43	27.8	28.8	40	24.8	21.1	26	20.1	30	NS
200.00	28.7	27.5	29.0	42.8	49.8	39.8	40.8	47.8	37.8	24.8	40	21.8	22.8	37	18.8	19.0	25	18.0	27	NS
250.00	32.6	31.0	32.8	41.3	48.3	38.3	39.3	46.3	36.3	22.8	37	19.8	20.8	34	16.8	18.3	25	17.3	26	NS

Characteristic Impedance	100±6 Ohm @ 1-250 MHz
Resistance Unbalance	2% max.
Capacitance	45 pF/m nom. @ 1 KHz
Cap. Unbalance (Wire to Ground)	1500 pF/Km max. @ 1 KHz.
Voltage Rating	72 Vdc max.
Dielectric Strength	1500 Volts/1 minute min rms
Velocity of Propagation (NVP)	67-69%
Propagation Delay	514 + 36/f ^{1/2} nS/100m max @ 1-300 MHz
Propagation Delay Skew	35 nS/100m max @ 1-300 MHz
Insulation Resistance	5000 MegaOhm.Km min. @ 500 Vdc
Coupling Attenuation	40 dB min @ 30-100 MHz 40-20Log(f/100) @100-300 MHz
Transfer Impedance	N/A

ORDERING INFORMATION

HCS P/N	Description	OD mm	Weight Kg/Km	Packaging	Notes
H06-00465-DK	4x2x23# U/UTP CAT 6 Outdoor Black	8.0	57	305m Drum	-
H06-00465-DP	4x2x23# U/UTP CAT 6 Outdoor Black	8.0	57	500m Drum	-
H06-00465-DM	4x2x23# U/UTP CAT 6 Outdoor Black	8.0	57	1000m Drum	-
H06-00465-DR	4x2x23# U/UTP CAT 6 Outdoor Black	8.0	57	2000m Drum	-
H06-00465-DT	4x2x23# U/UTP CAT 6 Outdoor Black	8.0	57	3000m Drum	-