

Category 7+ S/FTP 100 Ohm  
Horizontal LAN Cables  
Tested to 1000 MHz

**DataLink 600**

**TRANSMISSION PROPERTIES AND ELECTRICAL SPECIFICATIONS**

FREQ.	Insertion Loss	NEXT	PS NEXT	EL FEXT	PS EL FEXT	RL	TCL	EL TCL	PS ANEXT	PS AFEXT
MHz	dB/100m	dB	dB	dB/100m	dB/100m	dB	dB	dB	dB	dB
	Max	Min	Min	Min	Min	Min	Min	Min	Min	Min
1	NS	78.0	75.0	78.0	75.0	20.0	40.0	35.0	67.0	67.0
4	3.74	78.0	75.0	83.3	80.3	23.0	40.0	23.0	67.0	67.0
8	5.24	78.0	75.0	77.2	74.2	24.5	40.0	16.9	67.0	67.0
10	5.86	78.0	75.0	75.3	72.3	25.0	40.0	15.0	67.0	67.0
16	7.41	78.0	75.0	71.2	68.2	26.0	38.0	10.9	67.0	67.0
20	8.29	78.0	75.0	69.3	66.3	25.0	37.0	9.0	67.0	67.0
25	9.29	78.0	75.0	67.3	64.3	24.3	36.0	7.0	67.0	65.2
31.25	10.41	78.0	75.0	65.4	62.4	23.6	35.1	5.1	67.0	63.3
62.5	14.88	75.5	72.5	59.4	56.4	21.5	32.0	NS	67.0	57.3
100	19.02	72.4	69.4	55.3	52.3	20.1	30.0	NS	67.0	53.2
150	23.56	69.8	66.8	51.8	48.8	18.9	28.2	NS	67.0	49.7
200	27.47	67.9	64.9	49.3	46.3	18.0	27.0	NS	67.0	47.2
250	30.97	66.4	63.4	47.3	44.3	17.3	26.0	NS	67.0	45.2
300	34.19	65.2	62.2	45.8	42.8	17.3	NS	NS	67.0	43.7
400	40.01	63.4	60.4	43.3	40.3	17.3	NS	NS	67.0	41.2
500	45.26	61.9	58.9	41.3	38.3	17.3	NS	NS	67.0	39.2
600	50.10	60.7	57.7	39.7	36.7	17.3	NS	NS	65.8	37.6
700	54.63	59.7	56.7	38.4	35.4	16.6	NS	NS	64.8	36.3
800	58.92	58.9	55.9	37.2	34.2	16.1	NS	NS	64.0	35.1
1000	66.93	57.4	54.4	35.3	32.3	15.1	NS	NS	62.5	33.2

Note: Values above 600MHz are nominal, for reference only

Characteristic Impedance	100±5 Ohm @ 1-1000 MHz
Resistance Unbalance	2% max.
Capacitance	45 pF/m nom. @ 1 KHz
Cap. Unbalance (Wire to Ground)	1500 pF/Km max. @ 1 KHz.
Voltage Rating	72 Vdc max.
Dielectric Strength	700 Volts/1 minute min rms
Velocity of Propagation (NVP)	77-80%
Propagation Delay	500 + 36/f/2 @ 1-1000 MHz.
Delay Skew	25 nS/100m max @ 1-1000 MHz.
Insulation Resistance	5000 MegaOhm•Km min. @ 500 Vdc
Coupling Attenuation	85 dB min @ 30-100 MHz 85-20Log(f/100) @100-600 MHz
Screening Attenuation	60 dB min @ 30-600 MHz
Transfer Impedance	10 mOhm/m max @ 1-30 MHz 30 MOhm/m max @ 30-100 MHz

**ORDERING INFORMATION**

HCS P/N	Description	OD mm	Weight Kg/Km	Cal. Value Kj/m	Packaging	Notes
H07-F0411-DP	4x2x23# S/FTP CAT 7+ PVC Gray, Tested to 1000 MHz	7.0	48	660	500m Drum	
H07-F0411-DM	4x2x23# S/FTP CAT 7+ PVC Gray, Tested to 1000 MHz	7.0	48	660	1000m Drum	
H07-F0412-DP	4x2x23# S/FTP CAT 7+ LS0H Gray, Tested to 1000 MHz	7.0	48	660	500m Drum	
H07-F0412-DM	4x2x23# S/FTP CAT 7+ LS0H Gray, Tested to 1000 MHz	7.0	48	660	1000m Drum	
H07-F0813-DP	2x(4x2x23#) CAT 7+ S/FTP PVC Gray,Tested to 1000 MHz	7.0x14.2	100	1320	500m Drum	FIG-8
H07-F0813-DM	2x(4x2x23#) CAT 7+ S/FTP PVC Gray,Tested to 1000 MHz	7.0x14.2	100	1320	1000m Drum	FIG-8
H07-F0814-DP	2x(4x2x23#) CAT 7+ S/FTP LS0H Gray, Tested to 1000 MHz	7.0x14.2	100	1320	500m Drum	FIG-8
H07-F0814-DM	2x(4x2x23#) CAT 7+ S/FTP LS0H Gray, Tested to 1000 MHz	7.0x14.2	100	1320	1000m Drum	FIG-8

Flame Test Conformance F=0: IEC 60332-1 F=B: IEC 60332-3-22 F=C: IEC 60332-3-24 F=D: IEC 60332-3-25

Note: Standard Jacket Color: Light Gray RAL 7035. Other colors available upon request.