

Category 6E
Unshielded RJ-45 Copper
Angled Patch Panels (Jacks)



TRANSMISSION AND ELECTRICAL SPECIFICATIONS

FREQ.	Insertion Loss	NEXT	FEXT	RL
MHz	dB/100m	dB	dB	dB
	Max	Min	Min	Min
1.00	0.02	85.0	84.0	53.0
4.00	0.02	81.0	75.0	54.0
8.00	0.02	78.0	70.0	56.0
10.00	0.03	77.0	68.0	57.0
16.00	0.03	73.0	58.0	58.0
25.00	0.04	70.0	60.1	60.0
31.25	0.04	68.0	59.0	57.0
62.50	0.05	64.0	53.0	44.0
100.00	0.06	60.0	49.0	34.0
200.00	0.06	55.0	43.0	23.0
250.00	0.08	52.0	41.0	20.0

Propagation Delay	2.5 nS max @ 1-250 MHz
Propagation Delay Skew	1.25 nS max @ 1-250 MHz
Current Rating	1.5 A max.
Contact Resistance	20 mOhm max (per contact) Initial Contact Resistance: 2.5 mOhm.
Input/Output Resistance	200 mOhm max
Input/Output Resistance Unbalance	50 mOhm max
Voltage Rating	72 Vdc max
Dielectric Strength	1000 Volts rms for 1 minute
Insulation Resistance	100 MegaOhm min @ 500 Vdc
DC Resistance	0.1 Ohm max @ 20C
TCL	28-20·Log(f/100) dB min @ 1-250 MHz
Transfer Impedance	N/A

ORDERING INFORMATION

HCS P/N	Description	Blocks	Units	Size		T568
				mm	Inch	
P6E-02404-1U	24 port RJ-45 Unshielded Angled CAT 6E 19" Patch Panel	110 IDC	1U	44.5x483	1.75x19	UNI
P6E-04804-2U	48 port RJ-45 Unshielded Angled CAT 6E 19" Patch Panel	110 IDC	2U	89x483	3.5x19	UNI