



Description

HCS DataLink Blank RJ-45 Keystone-Jack Copper Patch Panels series includes high quality empty multi-port panels specially designed for structured premise cabling in local area networks (LANs).

HCS DataLink blank panels are available with plastic or metal frames, with up to 48 ports and with standard or staggered form.

The plastic-frame panels are recommended for use with unshielded jacks, while the metal-frame panels are recommended for use with shielded jacks, in order to provide continuous ground connection even when non-shielded cords are used.

The HCS Logo and the DataLink Trademark ensure long lasting high-performance and full compatibility with all HCS components.

Applications

Installation of copper cabling systems in horizontal or vertical environments.

Benefits & Features

- ➔ Exceptional material properties and design - Providing a unique Century™ Lifetime Warranty.
- ➔ Integrated full installation accessories (supplied free of charge), including labels and icons, clip organizers and T-raps - Providing a simple and elegant cable termination and identification.
- ➔ Optional plastic front panels - Providing custom color selection.
- ➔ Detailed installation manual in English and Turkish - Providing clear and comprehensive instructions.
- ➔ Optional back-side cable management with clip organizer and trap connection - Providing simple and easy cable handling.
- ➔ High quality metal casing - Providing excellent EMC (Electro Magnetic Compatibility), minimizing radiation and maximizing noise immunity.
- ➔ Robust and installer-friendly design - Providing reduced installation and operating costs
- ➔ Unique DoubleSafe™ Quality Assurance Program - Providing lowest rejection rate available.

GENERAL PROPERTIES

Material of Construction - Metal Frame	Steel, Aluminum, Aluminum Alloy or Anodized Aluminum.
Paint and Color - Metal Frame	Powder paint finish, Black (Gray available upon request)
Connector Module Holder	High impact, Flame-retardant plastic compound, UL 94 V-0.
Material of Construction - Plastic Frame	High impact, Flame-retardant plastic compound, UL 94 V-0.
Packaging	One unit per box.
Environmental Conditions	-40 to +60C at 0-90% RH (Non condensing)
Storage Temperature	-20 to +80C
Non Halogen Constructions	Available upon request.

ORDERING INFORMATION

HCS P/N	Description	Features	Units	Jack Compatibility		Size	
				Unshielded	Shielded	mm	Inch
P00-02420-1U-B	24 port Keystone Jack Blank 19" Metal Patch Panel	Modular rear organizer	1u	Yes	Yes	44.0x483	1.75x19
P00-02430-1U	24 port Keystone Jack Blank 19" Staggered Metal Patch Panel	Modular rear organizer	1u	Yes	No	44.5x483	1.75x19
P00-02450-1U	24 port Keystone Jack Blank 19" Metal Patch Panel	Fixed rear organizer	1u	Yes	No	44.5x483	1.75x19
P00-02460-1U	24 port Keystone Jack Blank 19" Angled Metal Patch Panel	Modular rear organizer	1u	Yes	No	44.5x483	1.75x19
P00-02470-1U	24 port Keystone Jack Blank 19" Angled Metal Patch Panel	Modular rear organizer	1u	Yes	Yes	44.5x483	1.75x19
P00-02490-1U	24 port Keystone Jack Blank 19" Metal Patch Panel	Modular rear & front organizer	1u	Yes	No	44.5x483	1.75x19
P00-04810-2U	48 port Keystone Jack Blank 19" Plastic Patch Panel	Fixed rear organizer	2u	Yes	No	89x483	3.5x19
P00-04810-1U	48 port Keystone Jack Blank 19" Plastic Patch Panel	-	1u	Yes	No	44.5x483	1.75x19
P00-04850-1U	48 port Keystone Jack Blank 19" Metal HD Patch Panel	Modular rear organizer	1u	No	Yes	44.5x483	1.75x19
P00-024Z0-AU	24 port Keystone Jack Blank 19" Metal Patch Panel	Modular rear organizer	0.5u	No	Yes	22.2x483	0.87x19