

Category 6E  
Shielded Tool-Less RJ-45  
Keystone Jacks

**DataLink 250E**

**TRANSMISSION AND ELECTRICAL SPECIFICATIONS**

FREQ.	Insertion Loss	NEXT	FEXT	RL
MHz	dB/100m	dB	dB	dB
	Max	Min	Min	Min
1.00	0.02	85.0	84.0	53.0
4.00	0.02	81.0	75.0	54.0
8.00	0.02	78.0	70.0	56.0
10.00	0.03	77.0	68.0	57.0
16.00	0.03	73.0	58.0	58.0
25.00	0.04	70.0	60.1	60.0
31.25	0.04	68.0	59.0	57.0
62.50	0.05	64.0	53.0	44.0
100.00	0.06	60.0	49.0	34.0
200.00	0.06	55.0	43.0	23.0
250.00	0.08	52.0	41.0	20.0

Propagation Delay	2.5 nS max @ 1-250 MHz
Propagation Delay Skew	1.25 nS max @ 1-250 MHz
Current Rating	1.5 A max.
Contact Resistance	20 mOhm max (per contact)
Input/Output Resistance	200 mOhm max
Input/Output Resistance Unbalance	50 mOhm max
Voltage Rating	72 Vdc max
Dielectric Strength	1000 Volts rms for 1 minute
Insulation Resistance	500 MegaOhm min @ 500 Vdc
DC Resistance	0.1 Ohm max @ 20C
TCL	28-20-Log(f/100) dB min @ 1-250 MHz
Transfer Impedance	0.1 Ohm @ 1 MHz, 0.2 Ohm @ 10 MHz, 1.6 Ohm @ 80 MHz max.

**ORDERING INFORMATION**

HCS P/N	Description	Orientation	Notes
J6E-00861	8P8C RJ-45 Shielded Tool-less Keystone Jack CAT 6E	90°	B
J6E-00862	8P8C RJ-45 Shielded Tool-less Keystone Jack CAT 6E	90°	A
J6E-00863	8P8C RJ-45 Shielded Tool-less Keystone Jack CAT 6E	90°	Universal